



The alternative system with closed design. EMPIRE is an optimal mat with wider profiles and modern design. Imagine your impressive entrance with Empire STILMAT doormat. For all buildings with high demands in regard to resilience and harmonious appearance. Suitable for outdoor use and for normal to heavy frequency of passengers. This model is with profiled rubber inserts and it is ideal for picking up coarse dirt. Anodized aluminum doormat model with 22mm height. The weather-proof solution among the robust solution.





Ideal for: Coarse dirt



The weather-proof solution



Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys




Aluminum coating: Fully anodized



Logo options: Logo engraving







STILMAT EMPIRE

Rubber - closed

Code: TCR

Model	Empire (Rubber)
Tread surface (inlay):	Profiled rubber inserts. Weather-proof
Ideal for	Coarse dirt
Colors:	Black, Grey, Brown
Version	Closed system
Code	TCR
Approx. height (mm)	22
Entrance position	Outdoor
Zones: I - II - III	Zone: I
Load	Heavy
Footfall	Daily footfall up to 2000
Roll-over and drive-over capability:	Wheelchairs, Prams, Hand and Light shopping trolleys
Support chassis	Made from rigid anodized aluminum with rubber sound insulation underlay
Aluminum coating:	Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.
Aluminum material thickness (mm)	1.2
Connection	Strong PVC connection strip, the entire width
Standard profile clearance approx. (mm)	0 mm
Slip resistance	R 9 slip resistance as per DIN 51130
Max width/profile length for each individual section (mm):	6000
Max depth/walking depth for individual units (mm):	Any
Mat divisions as per factory standards or customer specifications	Recommended maximum mat weight of 45 kg
Depth for individual units (mm):	Cca 22
Stationary load kg/100cm²	2200
Weight (kg/m²)	Cca 20
Logo options	Logo engraving, rubber logo, LED logo
Contact	STILMAT

Guarantee: 5 years on aluminum parts and construction

