

1
ZONE


24
HEIGHT (mm)




STILMAT KING

Lux Brush - open

Code: NOB



The KING is one of the base models of aluminum doormats, where profiles are connected with galvanized steel cable and rubber spacers. It is an alternative way of connection. Different and strong look. Proven design, rigid profiles. Profile standard clearance of 5 mm, or 3 mm available as an option for revolving door drives, in accordance with EN 16005. Imagine your impressive entrance with KING STILMAT doormat. Suitable for outdoor use and for extreme frequency of passengers. This model is with thorough brushes for an extra cleaning effect. Ideal for picking up coarse dirt.



Ideal for: Coarse dirt



The weather-proof solution




Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys



Aluminum coating: Fully anodized



Logo options: Logo engraving



STILMAT KING

Lux Brush - open

Code: NOB

Model	KING (Brush)
Tread surface (inlay):	Lux brushes recessed, robust. Weather-proof
Ideal for:	Coarse dirt
Colors:	Black, Grey
Version	Open system
Code	NOB
Approx. height (mm)	24
Entrance position	Outdoors
Zones: I – II - III	Zone: I
Load	Extreme
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
Footfall	Daily footfall of 2000 and up
Roll-over and drive-over capability:	Wheelchairs, Prams, Hand and Light shopping trolleys
Support chassis	Made from rigid anodized aluminum with rubber sound insulation underlay
Aluminum coating:	Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.
Aluminum material thickness (mm)	1.2
Connection	Galvanized steel cable and rubber spacers
Standard profile clearance approx. (mm)	5 mm (or 3mm for automatic/revolving doors)
Slip resistance	R 13 slip resistance as per DIN 51130
Max width/profile length for each individual section (mm):	6000
Max depth/walking depth for individual units (mm):	Any
Mat divisions as per factory standards or customer specifications	Recommended maximum mat weight of 45 kg
Depth for individual units (mm):	Cca 24
Stationary load kg/100cm ²	2200
Weight (kg/m ²)	Cca 20
Logo options:	Logo engraving
Contact	STILMAT

Guarantee: 5 years on aluminum parts and construction