

STILMAT ROYAL

Rubber - closed

Code: RCR

Description:	Closed hardwearing aluminum entrance mat for laying on the floor. Custom produced mats to fit width and walking depth specifications perfectly. Suitable for wheeled traffic. Any geometric shape is available on demand.
Model	ROYAL (Rubber)
Tread surface (inlay):	Profiled rubber inserts
Ideal for	Coarse dirt
Colors:	Black, Grey, Brown...
Version	Closed system
Code	RCR
Approx. height (mm)	17 mm
Entrance position	Outdoors
Zones: I – II - III	Zone: I
Load	From Normal to Heavy
Footfall	Daily footfall up to 1500
Roll-over and drive-over capability:	Wheelchairs, Prams, Hand and Light shopping trolleys
Support chassis	Made from rigid anodized aluminum with rubber sound insulation underlay
Aluminum coating:	Fully anodized, to increase resistance to corrosion and wear. More aesthetically pleasing finish and harder surface than pure aluminum.
Aluminum material thickness (mm)	1.2
Connection	Strong PVC connection strip, the entire width
Standard profile clearance approx. (mm)	0 mm closed system
Slip resistance	R 9 slip resistance as per DIN 51130
Logo options	Logo engraving, rubber logo, LED logo
Contact	STILMAT

Guarantee: 5 years on aluminum parts and construction