



ZONE




HEIGHT (mm)

STILMAT VICE PRESIDENT

Ribbed carpet - open

Code: VOL



The VICE PRESIDENT is an aluminum doormat with the most in demand height and it is a "budget-friendly" model. With its proven design and rigid profiles it meets the basic characteristics of similar Stilmat doormat models. Imagine your impressive entrance with VICE PRESIDENT STILMAT doormat. Suitable for internal use and for extreme frequency of passengers. This model is with high quality ribbed carpet ideal for picking up fine dirt and moisture. Anodized aluminum doormat model with 23mm height. The weather-proof solution among the robust solution.



Ideal for: Fine dirt and moisture



The weather-proof solution




Roll-over and drive-over capability: Wheelchairs, Prams, Hand and Light shopping trolleys



Aluminum coating: Fully anodized



Logo options: Logo engraving



STILMAT VICE PRESIDENT

Ribbed carpet - open

Code: VOL

Model	VICE PRESIDENT (Ribbed carpet)
Tread surface (inlay):	High quality ribbed carpet for Public buildings (A+EFL) , durable and luxurious character. Made from 100% Polyamide with gel backing. Weather-proof
Ideal for	Fine dirt and moisture
Colors:	Black, Grey, Brown...
Version	Open system
Code	VOL
Approx. height (mm)	23
Entrance position	Indoors
Zones: I – II - III	Zone: III
Load	Extreme
Footfall	Daily footfall of 2000 and up
Roll-over and drive-over capability:	Wheelchairs, Prams, Hand and Light shopping trolleys
Support chassis	Made from rigid aluminum with foam sound insulation underlay
Aluminum material thickness (mm)	1.2
Connection	Strong and flexible PVC connection strip, the entire width
Standard profile clearance approx. (mm)	5 mm (or 3mm for automatic/revolving doors)
Slip resistance	R 11 slip resistance as per DIN 51130
Max width/profile length for each individual section (mm):	6000
Max depth/walking depth for individual units (mm):	Any
Mat divisions as per factory standards or customer specifications	Recommended maximum mat weight of 45 kg
Depth for individual units (mm):	Cca 23
Stationary load kg/100cm ²	2200
Weight (kg/m ²)	Cca 20
Logo options	Logo engraving
Contact	STILMAT

Guarantee: 5 years on aluminum parts and construction