



STILMAT CODE™ STANDARD


Code: CO-DCC



The CODE STILMAT™ is ideal for heavy use in entrance areas, stairwells, pantries and lifts, amongst others. Premium quality (class 33). Commercial buildings and medium-sized and large offices can benefit from the scraping and absorbing function of the CODE STILMAT™ on a daily basis. It can be used as an inlay for any STILMAT aluminum doormat model, indoor mat or runner rug.

Description

Special and high quality Dust Control Carpet Rug for covered and indoor areas. Suitable for intensive covered and indoor foot traffic – entrance areas, halls, stairwells, lifts.... Enduring dirt-concealing capabilities and hard-wearing.



- Better Scraping – where moisture absorption and dirt scraping are key considerations.
- Anti static - dirt and moisture are stopped and absorbed
- Absorption capacity – 5.13 l/m²
- Total weight 3.650g/m²
- Savings on cleaning cost up to 65% are possible
- Fine dirt in the air will be prevented and considerable cost in cleaning avoided
- Health - Improves indoor air quality (Sick building syndrome)
- Flammability – Fire Safety - Euroclass 13501 (Norm Cfl-s1)
- Slip resistance EN13893 – DS
- Reduces noise levels – Height 9 mm with heavy coating PVC backing
- High quality yarn – Velour structure with a high pile. The pile design, comprising both coarse and soft yarns
- Rubber border/edge – upon request
- Luxury appearance - dirt is barely visible thanks to the combined yarns. Fits in any interior
- Made in Netherlands




STILMAT CODE™ STANDARD


Code: CO-DCC



Model	CODE
Group	Indoor, High traffic, super absorbing
Code	CO-DCC
Pile material	100% Polyamide
Backing	PVC
Primary backing	Nonwoven PET/PA
Yarn construction	Velour
Pattern	Blended
Colors	6
Pile weight ISO 8543	± 850 gram/m ²
Total weight ISO 8543	± 3.650 gram/m ²
Pile height ISO 1766	± 7.5 mm
Total height ISO 1765	± 9 mm
Pile density ISO 8543	0,103 g/cm ³
Number of stitches ISO 1763	± 70.900 /m ²
Use classification EN 1307	33
Wearing class EN 1963	33
Comfort EN 1307	LC2
Suitability for stairs EN 1963	Intensive use
Suitability for castor chairs EN 985	Intensive use
Dimension stability ISO 2551	<0,3%
Light fastness ISO 105 B02	>6
Water fastness ISO 105 B01	4-5
Rubbing fastness ISO 105 X12	4-5
Salt water ISO 105 E02	4-5
Shampoo BS 1006	4-5
Organic solvents ISO 105 X05	4-5
Absorption capacity TNO W6034	+ 5.13 l/m ²
Flammability Euroclass EN13501	Cfl /s1
Slip Resistance EN13893	DS
Static charge ISO 6356	0.4 kV
Sand absorption 1-3	3
Optical class 1-5	4,5
Sizes rolls	2000mm Width
Rubber border/edge	Upon request
Quality class	33 Luxury, for commercial buildings
Ideal position on entrance	Covered or indoor space with high traffic
Zone: I – II – III	II, III
Cleaning	Dirt removal with powerful brush vacuum cleaner. The spray extraction process is recommended for periodic basic cleaning. Cleaning with plenty of water is absolutely no problem, water temperature should not be above 40°C. Do not use chlorinated hydrocarbon (Tetra).




Black 990




Beige 991




Brown 995



Blue 996



Grey 998



Red 999

	High traffic	Medium traffic
Not combined with outdoor matting	A	B
Combined with outdoor matting	C	D
Outdoor matting	E	