



STILMAT LOMBOK® RIBBED CARPET INLAY FOR DOORMATS

Code: LB

Ribbed carpet with premium quality. Keeps and absorbs dirt and moisture. Great for any entrance in commercial areas with high frequency.

Description

The LOMBOK® is ideal for heavy use in entrance areas, stairwells, pantries and lifts, amongst others. Commercial buildings and medium-sized and large offices can benefit from the scraping and absorbing function of the LOMBOK® on a daily basis.... Enduring dirt-concealing capabilities and hard-wearing. It is used as an inlay for any STILMAT® aluminum doormat model, or in combination with rubber or lux brush inlays in any STILMAT® aluminum doormat. With VOC standard A+ (equal with AgBB).



- High quality for commercial buildings
- VOC- A+ standard - which is the highest assessment of the quality of construction products in terms of emission potential
- Anti static - dirt and moisture are stopped and absorbed
- Good absorption capacity
- Total weight 2.100 g/m²
- Savings on cleaning cost up to 65% are possible
- Fine dirt in the air will be prevented and considerable cost in cleaning avoided
- Flammability – Fire Safety - EFL
- Health - Improves indoor air quality (Sick building syndrome)
- Slip resistance EN13893 – DS
- Reduces noise levels – Height 10 mm with heavy coating GEL backing
- High quality yarn – Ribbed structure with a high pile. The pile design, comprising both coarse and soft yarns
- Luxury appearance - dirt is barely visible thanks to the combined yarns. Fits in any interior
- Made in Belgium (EU)



STILMAT LOMBOK®

RIBBED CARPET INLAY FOR DOORMATS

Code: LB

Model	LOMBOK® - Ribbed carpet with gel backing
Group	Indoor and covered areas inlays
Code	LB
Pile material	100% Polypropilene
Standard VOC	A+
Backing	Latex gel
Primary backing	PP
Yarn construction	Ribbed (Cut-loop)
Pattern	Blended
Colors	4
Pile weight ISO 8543	± 1.500 gram/m ²
Total weight ISO 8543	± 2.100 gram/m ²
Pile height ISO 1766	± 4.5 mm
Total height ISO 1765	± 10 mm
Flammability	EFL
Slip Resistance EN13893	DS
Sizes rolls	2000mm width, 25000mm lenght
Rubber border/edge	Upon request
Quality class	Luxury, for commercial buildings
Ideal position on entrance	Covered or indoor space with high traffic
Zone: I – II – III	II, III
Cleaning	Dirt removal with powerful brush vacuum cleaner. The spray extraction process is recommended for periodic basic cleaning. Cleaning with plenty of water is absolutely no problem, water temperature should not be above 40°C. Do not use chlorinated hydrocarbon (Tetra).



Black



Brown



Grey

	High traffic	Medium traffic
Not combined with outdoor matting	A	B
Combined with outdoor matting	C	D
Outdoor matting	E	

