

STILMAT CODE™ STANDARD

Code: CO-DCC

Description Model	Special and high quality Dust Control Carpet mat, rug or inlay, for covered and indoor areas. Suitable for intensive covered and indoor foot traffic, where moisture absorption and dirt scraping are key considerations. CODE STILMAT - doormat, rug, inlay
Code	CO-DCC
Characteristics	Indoor, super absorbing and scraping
Pile material	100% Polyamide
Backing	PVC
Primary backing	Nonwoven PET/PA
Yarn construction	Velour
Pattern	Blended
Total weight ISO 8543	Min 3.600 gram/m ²
Total height ISO 1765	Min. 8.5 mm
Use classification EN 1307	Min. 33
Wearing class EN 1963	Min. 33
Comfort EN 1307	Min. LC2
Traffic class	Recommended for high intensive foot traffic
Absorption capacity TNO W6034	Min. 5.0 l/m ²
Flammability Euroclass EN13501	Min. Cfl /s1
Slip Resistance EN13893	Min. DS
Sand absorption 1-3	Min. 3
Optical class 1-5	Min. 4.5
Sizes rolls	Up to 2000mm Width, 25000mm length
Rubber border/edge	Upon request
Quality class	33 For Luxury and commercial buildings
Ideal position on entrance	Covered or indoor space with high traffic
Zone: I – II – III	II, III
Country of origin	Netherlands (EU)
Contact	STILMAT