

# STILMAT PREMIUM™ STANDARD

Code: PR-DCC

<b>Description</b>	<b>The mat features a bouclé construction. In this kind of composition the pile material is formed out of looped pile. Combined with the blended design this makes small patches of dirt invisible. The strong and resistant pile is made up of different yarns to allow moisture absorption and dirt scraping.</b>
Model	PREMIUM STILMAT - doormat, rug, inlay
Code	PR-DCC
Characteristics	Indoor, super absorbing and scraping
Pile material	100% Polyamide
Backing	PVC
Primary backing	Nonwoven PET/PA
Yarn construction	Bouclé
Pattern	Blended
Total weight ISO 8543	Min 3.550 gram/m <sup>2</sup>
Total height ISO 1765	Min. 7.0 mm
Use classification EN 1307	Min. 32
Wearing class EN 1963	Min. 32
Comfort EN 1307	Min. LC3
Traffic class	Recommended for high intensive foot traffic
Absorption capacity TNO W6034	Min. 5.1 l/m <sup>2</sup>
Flammability Euroclass EN13501	Min. Cfl /s1
Slip Resistance EN13893	Min. DS
Sand absorption 1-3	Min. 2
Optical class 1-5	Min. 4.5
Sizes rolls	Up to 2000mm Width, 25000mm length
Rubber border/edge	Upon request
Quality class	For Luxury and commercial buildings
Ideal position on entrance	Covered or indoor space with high traffic
Zone: I – II – III	II, III
Country of origin	Netherlands (EU)
Contact	STILMAT